

1/15




FIG. 1




FIG. 2

2/15




FIG. 3
 PRIOR ART

3/15




FIG. 4
 PRIOR ART

4/15






FIG. 5




6/15

PERFORMANCE OF DIFFERENT RECEIVERS IN THE PRESENCE OF
WHITE NOISE AND MULTIPATH REFLECTION

A. SQUARE LAW DETECTOR RECEIVER



B. DIRECT CONVERSION RECEIVER



C. ULTRA-WIDEBAND PULSE TEMPLATE CORRELATION RECEIVER
CONSTRUCTED ACCORDING TO ONE EMBODIMENT OF THE PRESET INVENTION



FIG. 7




FIG. 8






FIG. 9

9/15

10C. PULSE SAMPLING



10A. PULSE SIGNAL COARSE ACQUISITION PROCESS



10B. PULSE SIGNAL FINE ACQUISITION METHOD






FIG. 10

ULTRA-WIDEBAND (UWB) PULSE ACQUISITION PROCESS IN
 PRESENCE OF MULTIPATH AND NOISE



A) N UWB Pulse is Detected - UWB Pulse Sequence Energy is Near
 Zer ; Synchronization Loop is Unlocked



B) Weak Multi-path UWB Pulse is Detected - UWB Pulse Sequence
 Energy is increased; Synchronization Loop is Unlocked

FIG. 11

11/15





FIG. 12

12/15

FIG. 13



13/15





FIG. 14

14/15

15A. Quadrature Correlator- M-ary PSK Detection



15B. Detection of M-ary PPM /OOK MODULATION




FIG. 15

15/15




FIG. 16